

Woven Cotton Electrical Tape									
Style	Thickness	Width		Weave Pattern	Total Warp Ends	Filling / Picks		Pounds / Linear Yard	
		Inches	mm			Inches	cm		
6863	0.005" 0.013mm	0.375"	9.5	Plain	28	36	14	0.002	Meets ASTM A1 Standards
6864		0.5"	12.7		40			0.0027	
6865		0.625"	15.9		48			0.0033	
6866		0.75"	19.1		56			0.0039	
6868		1"	25.4		72			0.0051	
7862	0.007" 0.018mm	0.25"	6.35	Plain	22	30	12	0.0017	Meets ASTM A2 Standards
7863		0.375"	9.5		30	30	12	0.0024	
7864		0.500"	12.7		42	34	13	0.0033	
7865		0.625"	15.9		56	30	12	0.0038	
7866		0.750"	19.1		56	30	12	0.0044	
7868		1.00"	25.4		72	30	12	0.0057	
78610		1.25"	31.75		92	30	12	0.0073	
78612		1.50"	38.1		108	30	12	0.0086	
78616		2.00"	50.8		144	30	12	0.0114	
7863 36		0.375"	9.5		30	36	14	0.0025	
7864 36		0.500"	12.7		42	36	14	0.0034	
7866 36		0.75"	19.1		56	36	14	0.0047	
7868 36		1.00"	25.4		92	36	14	0.0061	
6433	0.007" 0.018mm	0.375"	9.5	Plain	36	25	8	0.0026	Meets ASTM A3 Standards
6434		0.500"	12.7		30	25	10	0.0022	
6436		0.750"	19.1		46	25	10	0.0037	
6438		1.00"	25.4		62	25	10	0.0049	
64312		1.50"	38.1		92	25	10	0.0073	
64312D10		1.50"	38.1		108	25	10	0.0083	
6438 D9	1.00"	25.4	72	25	10	0.0056			
6424 20	0.007" 0.018mm	.500"	12.7	Plain	36	20	8	0.0026	Light Weave
6426 17		.750"	19.1		46	18	7	0.0034	
6428 17		1.00"	25.4		62	18	7	0.0045	
64210		1.25"	31.75		74	18	7	0.0054	
64212		1.50"	38.1		92	18	7	0.0066	
64216		2.00"	50.8		120	18	7	0.0087	
303	0.011" 0.28mm	0.375"	9.5	Plain	25	30	12	0.0044	Tight Weave
304		0.500"	12.7		29			0.0045	
306		0.750"	19.1		44			0.0067	
308		1.00"	25.4		60			0.0091	
3012		1.50"	38.1		88			0.0134	
3016		2.00"	50.8		120			0.0181	

Woven Cotton Binding Tape									
Style	Thickness	Width		Weave Pattern	Total Warp Ends	Filling / Picks		Pounds / Linear Yard	
		Inches	mm			Inches	cm		
5144	0.013" 0.33mm	0.5"	12.7	Herringbone	52	38	15	0.0043	Meets ASTM B-1 Standards
5146		0.75"	19.1		74			0.0062	
5148		1"	25.4		94			0.0079	
51412		1.5"	38.1		140			0.0118	
51416		2"	50.8		160			0.0140	
9244	0.020" 0.50mm	0.5"	12.7	Herringbone	40	38	15	0.0067	Meets ASTM B-2 Standards
9246		0.75"	19.1		60			0.0100	
9248		1"	25.4		80			0.0125	
92412		1.5"	38.1		120			0.0187	
92416		2"	50.8		160			0.0250	
904	0.030" 0.76mm	0.5"	12.7	NonElastic	60	38	15	0.0088	Meets ASTM C-1 Standards
906		0.75"	19.1		80			0.0119	
908		1"	25.4		100			0.0145	
9012		1.5"	38.1		150			0.0225	
9016		2"	50.8		204			0.0302	
8044	0.022" 0.56mm	0.5"	12.7	Herringbone	40	38	15	0.007	
8046		0.75"	19.1		60			0.0107	
8048		1"	25.4		80			0.0145	
80412		1.5"	38.1		120			0.0206	
80416		2"	50.8		130			0.0274	